

MAG A650GL



- Tam modüler tasarım, Yassı kablolar
- 80 Plus Gold sertifikası ile yüksek enerji verimliliği
- Aktif PFC tasarımı, Endüstriyel seviye koruma için OVP,OCP,OPP,OTP, SCP,UVP
- 120mm Akışkan Dinamik Rulmanlı Fan
- LLC Full Bridge Topolojisi ve DC-DC modül tasarımı

SPECIFICATIONS

MODEL NAME	MPG GUNGNIR 100
Front I/O Ports	2 x USB 3.0 + HD Audio / Mic
Drive Bays	2 x 3.5" (compatible with 2.5") + 4 x 2.5"
VGA Card Support	Max 400mm / 15.75 inch
CPU Cooler Support	Max 170mm / 6.69 inch
Power Supply	Standard ATX
WEIGHT (CARD)	169g
Radiator Compatibility	120 / 140 / 240 mm
Product Name	MEG PROSPECT 700R
Modular	Yes (full modular)
Case Form Factor	Mid-Tower
Motherboard Form Factor Support	EATX (up to 310mmx304.8mm) / ATX / M-ATX / ITX
I/O Ports	2x USB 3.2 Gen 1 Type-A 1x USB 3.2 Gen 2x2 Type-C 1x HD Audio 1x Mic
Fan Bearing	Fluid Dynamic Bearing
Drive Mount Support	2x 2.5" 2x 2.5"/3.5"
Dimensions	120mm x 120mm x 25.6mm
Expansion Slots	7
Maximum GPU Length	400mm / 15.75 inches
Power Watt	650W
Maximum CPU Cooler Height	185mm / 7.28 inches
Power Supply Support	Standard ATX, max up to 220mm (without 3.5" HDD tray installed)
Bearing Type	Hydro-Dynamic Bearing
Input Voltage	100~240 VAC
Rated Speed	500 - 1800 ±15% RPM
Air Flow	19.79 - 71.27 CFM
Fan Size Support	Front: Up to 3 x 120 mm / 3 x 140 mm Top: Up to 3 x 120 mm / 3 x 140 mm Rear: Up to 1 x 120 mm / 1x 140 mm Side: Up to 3 x 120 mm
ATX (24 pin)	1
Static Air Pressure	0.16 - 2.09 mm-H2O
Pre-installed Fan Size	Front: 3x 140mm ARGB Fan Rear: 1x 140mm ARGB Fan
Input Frequency	47-63Hz

Efficiency	80 PLUS Gold (up to 90%)
Connector	4-Pin PWM/DC
Pre-installed Fan Type	ARGB
Radiator Size Support	Front: 120 / 140 / 240 / 280 / 360 mm Top: 120 / 140 / 240 / 280 / 360 mm Rear: 120 / 140 mm Side: 120 / 240 / 360 mm
EPS (4+4 pin)	2
Life Expectancy	MTTF 150,000 Hours (25°C)
Fan Size	120 mm
PCI-E (6+2 pin)	4
Dimension	140 x 150 x 86 mm
SATA (15 pin)	6
PFC Type	Active PFC
PRODUCT DIMENSIONS (MM)	510(D) x 227(W) x 525(H) mm 20.08(D) x 8.94(W) x 20.67(H) inch
Net Weight	15.95 kg / 35.16 lbs
Protection	OCP / OVP / OPP / OTP / SCP / UVP
WEIGHT (PRODUCT / PACKAGE)	9.3 KG
MOLEX (4 pin)	4
Gross Weight	21.55 kg / 47.51 lbs
Note	Material: Left Side: Tempered Glass/ Right Side- Metal Vertical GPU Mount : Yes Touch Panel: Yes
FDD (4 pin)	1

MAG A650GL					
AC INPUT	100-240~, 10A , 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	54A	0.3A	2.5A
TOTAL POWER	100W	648W	3.6W	12.5W	
	650W				

CONNECTOR						
ATX (20+4 PIN)	EPS (4+4 PIN)	PCI-E5.0	PCI-E (6+2 PIN)	SATA	MOLEX (PERIPHERAL)	FDD
1	2	0	4	6	3	1